




APPLICATION



Dimension(mm)



(Standard size as reference, Overall Size is different and it depends on control capacity and function)

Heliport Light Controller

AL-HP-G

Controller use steel material 304 as enclosure with good waterproof, UV protection and surge protection device, so it can be used in very bad environments. It's used to turn ON and OFF all Heliport lighting.

Compliance

- ICAO and FAA regulations and CAP437 (offshore helipads)

Features

- Power supply available in 12VDC, 48VDC, 110VAC, 240VAC, etc
- Surge protection (anti lightning In 15KA/5, max 40KA)
- Main air switch for over voltage protection
- Automatic control is optional
- ON/OFF button for each group of light
- Flashing on the top of the controller for water proof

SPECIFICATIONS

AL-HP-G Heliport Light Controller

Electrical Characteristics

Operating Voltage

12VDC, 48VDC, 110VAC, 240VAC, etc

Control Capacity

Up to 7 Group of lights(others are optional)

Physical Characteristics

Body Material

stainless steel

Overall size(mm)

800 × 580 × 330 (Standard, others optional)

Installation size(mm)

710 × 550 × M10 (Standard, others optional)

Weight(kg)

20 (Standard, others optional)

Product Life Expectancy

≥ 10 years

Environmental Factors

Ambient Temperature(°C)

-55~70

Humidity

0~95%

Wind Speed

80m/s

Waterproof

IP65

Options Available

Air-To-Ground Radio Control(VHF)

Adjust light intensity

Wireless Remote Control

Automatic Control