



Johannesburg Branch  
**MIMIC COMPONENTS**  
Cape Town Branch  
Mimic Cape



# IoT Refrigeration Temperature Controller

N150-4R-IoT



Energy Saving




Connection to the cloud



LTE communication  
with fallback

High contrast  
display



The **N150 IoT** is an AlwaysOn controller, a pioneer in its category, developed for the management and control of refrigeration assets in a wide variety of environments.

Its reliable control algorithm, input and output capabilities, combined with continuous connectivity to **Sensify's** CoolerCloud platform and the power of AI-driven processing, enable highly efficient control, real-time alert generation, and remote monitoring and management of coolers.

This controller is ideal for obtaining usage and performance metrics of coolers, reporting theft or loss through geolocation, and configuring devices remotely to prevent or streamline technical service operations.





### Ease of Installation

Quick connection without the need for screws



### Batch Setup

Fast commissioning via USB with QuickTune software



### Simplified Diagnostics

Custom error LEDs



### Anti-flame Protection

Housing UL94V-2 according to IEC 60730-1 and IEC 60730-2-9



### Security Lock

Prevents unauthorized access to the SIM Card

## Technical Specifications

Specifications	
Dimensions	48 x 96 x 92 mm (1/8 DIN)
Panel Cutout	45 x 93 mm
Approximate Weight	230g
Power	
Voltage	100 to 240 Vac $\pm 1$ 0%, 50/60 Hz
Consumption	10 VA
Environmental Conditions	
Operating Temperature	-10 to 50 °C
Relative Humidity	Max. 80% at 30°C
Sensor	NTC thermistor, 10 k $\Omega$ @ 25 °C
Measuring Range	-40 to 90 °C
Measurement Accuracy	0,6 °C
Door Sensor	Dry Contact or Open Collector NPN

Outputs	
OUT1	SPDT relay, 1HP 250 Vac
OUT2	SPST-NO relay, 3A 250 Vac
OUT3 and OUT4	Triac, 0,5 A 250 Vac
Voltage Supervisor	
Measuring Range	150 to 250 Vac

Front Panel	IP65, PC UL94 V-2
Housing	IP20, PA6 + 30 % FV, V-0
Wifi Connection	ESP32 module, 802.11 b/g/n protocol (internal antenna)
Mobile Data Connection	GSM, LTE Cat M1 and LTE Cat NB1/2 (internal antenna)
USB Interface	2.0, CDC class, Modbus RTU protocol
Start of Operation	4 seconds after turning on the equipment
Connectors	Faston and KK
Certifications	IEC 60730-1 and IEC60730-2-9

### JHB Branch

Mimic Components, Address: 5 Ramsay Street, Booyens, 2091, Johannesburg. Switchboard: +27(0)11-689-5700 | WhatsApp: 071-979-9999  
PO Box 38493, Booyens, 2016, Johannesburg, South Africa. Email: info1@mimiccomponents.co.za | Website: www.mimiccomponents.co.za

### Cape Branch

Mimic Cape, Address: Unit 41A, Stella Park, 57 Stella Road, Montague Gardens, 7441, Cape Town. Switchboard: +27(0)21-551-8185  
WhatsApp: 071-979-9999. Po Box 36955, Chempet, 7442, Cape Town, South Africa. Email: info@mimic-cape.co.za | Website: www.mimic-cape.co.za